



NARROW LOW PROFILE END DUMP TRUCK

**MODEL
DT-33N**

33.0 metric tonne · 36.4 short ton payload — 19.6 m³ · 25.7 yd³ capacity



FEATURES

- Field-proven, articulated DUX DT-33N underground 4-wheel drive dump truck is well suited for hauling ore, waste and backfill on level and steep grades
- Excellent load retention and fast tramming up steep ramps guaranteed — highest power to weight ratio in its class
- Permits efficient chute, side and end loading in narrow drifts with low headings
- Clean and rapid discharge cycles guaranteed with 65° dump angle and smooth flow, wear resistant alloy steel dump box
- Electronically controlled engine reduces fuel consumption and ventilation requirement
- Equipped with 4-wheel POSI-STOP brake system for maximum safety, reliability and low maintenance cost
- Centralized service points and modular design for easy service access and fast component exchange
- Excellent service and parts back-up worldwide

WEIGHTS

Payload	33.0 tonne.....	36.4 ton
Machine weight, approx.....	27.2 tonne.....	30.0 ton
GVW	60.2 tonne.....	66.4 ton

SAE VOLUME*

Struck	16.4 m ³	21.5 yd ³
Heaped	19.6 m ³	25.7 yd ³
Loose ore density.....	1.8 t/m ³	3,035 lb/yd ³

*Custom box size to suit different ore weight available.

OVERALL DIMENSIONS

Length.....	10 235 mm.....	33' 7"
Width.....	3 050 mm.....	10' 0"
Height over box sides.....	2 515 mm.....	8' 3"
Height over canopy or cab	2 695 mm.....	8' 10"

TURNING RADIUS

Inside.....	4 850 mm.....	15' 11"
Outside.....	8 560 mm.....	28' 1"
Angle		42°

DISCHARGING

Height at maximum dump angle ...	5 285 mm.....	17' 4"
Maximum dump angle		65°



Available with optional automatic tailgate.

DUX Model DT-33N Narrow Low Profile End Dump Truck

TECHNICAL SPECIFICATIONS*

Engine

Make and model Cummins X12 electronic
Derated power 298 kW (400 HP) @ 2100 RPM
Cylinders 6
Aspiration Turbocharged CAC
Displacement 11.8 L 720 in³
Exhaust gas Ultra clean DPF (diesel particulate filter), DPR
after-treatment (diesel particulate recirculation), SCR (selective
..... catalytic reduction)
Air cleaner Direct flow air filter
Exhaust brake Part of VGT Turbo (variable geometry turbo)
Emission standard Meets EPA Tier 4 Final, Euro Stage V

Torque Converter

Make and model Dana SOH CL 8000 series, single stage with
..... automatic lock-up and flex plate drive

Transmission

Make and model Dana SOH 6000 series
Speeds 4 speeds in forward and reverse

Axles

Make and model Dana SOH 21D with high traction differential and
..... POSI STOP brakes on all 4 wheel ends

Tires

– Bridgestone 26.5R25, multi-star, L-4 VSNT radial

Brakes

Service and 4-wheel POSI-STOP totally enclosed multi-disc,
emergency/parking liquid cooled, spring applied hydraulically released
..... with its own independent circulating cooling
..... system and accumulator back-up
Automatic Brake Applies brake in case of engine failure or pressure
Applicator (ABA) drop in torque converter

Steering

– Articulated frame hydraulic power steering with pilot monostick control
– Double acting steering cylinders (2)
– $\pm 42^\circ$ steering angle each way for a total of 84°

Oscillation

– $\pm 10^\circ$ center of oscillation for a total of 20°
– Large sized, heavy-duty roller bearing for minimum maintenance and a
smooth ride, 4-wheel ground contact guaranteed

Frames and Pins

– Articulated heavy-duty frames made to withstand the high impact and
torsional stress associated with mining application
– Frames come with five-year unlimited hour guarantee
– Large high tensile alloy steel pins in replaceable anchor bushings

Dump Body

– Made from reinforced impact, wear resistant alloy steel plates,
substantially prolongs service life
– 65° dumping angle for clean and rapid discharge cycles

Operator Compartment

– Side seated for maximum visibility and bi-directional operation
– Heavy-duty adjustable suspension seat with arm rests and retractable
seat belt
– Shock mounted compartment floor for maximum comfort
– All controls and gauges are within easy reach and view of operator

Hydraulic System

– Heavy-duty double acting protected steering cylinders (2) with hard
chrome plated stems
– Heavy-duty double acting two-stage fully protected telescopic dump
cylinders (2) with hard chrome plated stems
– Heavy-duty PTO-driven variable displacement piston pumps with load
sensing driven from converter
– Suction filter
– Inline high pressure filter with service gauge
– $\frac{3}{4}$ " inside diameter and over hoses that are four-spiral wire braid and
have crimped hose end swivel fittings
– Hose bulk-head located mid-ship

Tank Capacities

Fuel 454 L 120 US gallons
Hydraulic oil 340 L 90 US gallons
Brake cooling oil 114 L 30 US gallons

Electrical System

– 24-volt negative ground
– 75 amp alternator with integrated sealed voltage regulator
– Main electric cut-off switch
– Heat resistant, waterproof, sealed electric PMA wire harness
– Sealed junction box and stainless steel instrument panel box with
multi-stem connectors
– Semi-automatic circuit breakers
– Front (4), rear (2), and all-directional (1) LED high-intensity lights
– Heavy-duty batteries (2)
– Signal horn and audible, adjustable back-up alarm

Standard Features

Cummins X12, EPA Tier 4 Final, Euro Stage V electronic engine • PRAN
display monitor includes digital fuel gauge • Automatic engine shut-off at
low oil pressure and high temperature • Hourmeter • All necessary gauges
for engine, converter and brake pressure • Wheel chocks (2) with storage
brackets (2) • 9 kg (20 lb) hand held fire extinguisher • Neutral engine
start protection • Centralized manual lubrication mid-ship • Dump box
and articulation safety bars • Parts/Operator/Maintenance manuals •
Compliant with MSHA, CANMET and CE regulation

Options

Different engine • Engine brake • Certified FOPS/ROPS canopy • Fully
equipped certified FOPS/ROPS noise suppression cab • Automatic
tailgate • Automatic lubrication system • Fire suppression system • Video
system • Ejector body • Spare rim assembly • Cold weather package •
Knock-down construction for lowering unit down mine shaft •
OTHER OPTIONS ON REQUEST



Manufactured by:

DUX MACHINERY CORPORATION

615 Lavoisier, Repentigny Quebec, Canada J6A 7N2

+1 450.581.8341 tel +1 450.581.5138 fax www.duxmachinery.com